

Package: jpmesh (via r-universe)

October 5, 2026

Type Package

Title Utilities for Japanese Mesh Code

Version 2.1.0.9000

Maintainer Shinya Uryu <suika1127@gmail.com>

Description Helpful functions for using mesh code (80km to 100m) data in Japan. Visualize mesh code using 'ggplot2' and 'leaflet', etc.

License MIT + file LICENSE

URL <https://uribo.github.io/jpmesh/>

BugReports <https://github.com/uribo/jpmesh/issues/>

Depends R (>= 4.1)

Imports leaflet (>= 1.1.0), memoise (>= 1.1.0), miniUI (>= 0.1.1), purrr (>= 0.2.4), rlang (>= 0.1.4), sf (>= 0.5-5), shiny (>= 1.0.5), tibble (>= 3.0.0), units (>= 0.5-1), vctrs (>= 0.3.4)

Suggests knitr (>= 1.20), lintr (>= 2.0.1), lwgeom (>= 0.1-4), testthat (>= 2.1.0), rmarkdown (>= 1.10), vdiffr (>= 0.3.1)

VignetteBuilder knitr

LazyData true

Encoding UTF-8

RoxygenNote 7.3.2

Roxygen list(markdown = TRUE)

Config/pak/sysreqs libabsl-dev cmake libgdal-dev gdal-bin libgeos-dev make libpng-dev libuv1-dev libssl-dev libproj-dev libsqlite3-dev libudunits2-dev zlib1g-dev

Repository <https://uribo.r-universe.dev>

Date/Publication 2025-01-27 08:33:50 UTC

RemoteUrl <https://github.com/uribo/jpmesh>

RemoteRef HEAD

RemoteSha 549f67525559fd91c35249e5f0350034a8f6b123

Contents

administration_mesh	2
coarse_gather	3
coords_to_mesh	3
eval_jp_boundary	4
export_mesh	5
fine_separate	5
is_mesh	6
jpnrect	6
mesh_convert	7
mesh_size	8
mesh_to_coords	9
mesh_viewer	9
meshcode_set	10
meshcode_sf	10
meshcode_vector	11
neighbor_mesh	12
rmesh	13
sf_jpmesh	13
Index	15

administration_mesh	<i>Extract administration mesh code</i>
---------------------	---

Description

Extract administration mesh code

Usage

administration_mesh(code, to_mesh_size)

Arguments

code	administration code
to_mesh_size	target mesh size. That is, 1 for 1km, and 0.5 for 500m. From 80km to 0.100km.

Examples

```
## Not run:
administration_mesh(code = "35201", to_mesh_size = 1)
administration_mesh(code = "08220", to_mesh_size = 80)
administration_mesh(code = c("08220", "08221"), to_mesh_size = 10)
administration_mesh(code = "35", to_mesh_size = 80)
administration_mesh(code = c("33", "34"), to_mesh_size = 80)

## End(Not run)
```

coarse_gather	<i>Gather more coarse mesh</i>
---------------	--------------------------------

Description

Return coarse gather mesh codes

Usage

```
coarse_gather(meshcode, distinct = FALSE)
```

Arguments

meshcode	character. mesh code
distinct	return unique meshcodes

Value

[meshcode](#)

Examples

```
m <- c("493214294", "493214392", "493215203", "493215301")
coarse_gather(m)
coarse_gather(coarse_gather(m))
coarse_gather(coarse_gather(m), distinct = TRUE)
```

coords_to_mesh	<i>Convert from coordinate to mesh code</i>
----------------	---

Description

From coordinate to mesh codes.

Usage

```
coords_to_mesh(longitude, latitude, to_mesh_size = 1, geometry = NULL, ...)
```

Arguments

longitude	longitude that approximately to .120.0 to 154.0 (double)
latitude	latitude that approximately to 20.0 to 46.0 (double)
to_mesh_size	target mesh size. That is, 1 for 1km, and 0.5 for 500m. From 80km to 0.100km.
geometry	XY sfg object
...	other parameters

Value

mesh code (default 3rd meshcode aka 1km mesh)

References

Akio Takenaka: http://takenaka-akio.org/etc/j_map/index.html # nolint

See Also

[mesh_to_coords\(\)](#) for convert from meshcode to coordinates

Examples

```
coords_to_mesh(141.3468, 43.06462, to_mesh_size = 1)
coords_to_mesh(139.6917, 35.68949, to_mesh_size = 0.250)
coords_to_mesh(139.71475, 35.70078)
coords_to_mesh(139.71475, 35.70078, to_mesh_size = 0.1)
coords_to_mesh(c(141.3468, 139.71475),
               c(43.06462, 35.70078),
               mesh_size = c(1, 10))
# Using sf (point as sfg object)
library(sf)
coords_to_mesh(geometry = st_point(c(139.71475, 35.70078)))
coords_to_mesh(geometry = st_point(c(130.4412895, 30.2984335)))
```

eval_jp_boundary

Check include mesh areas

Description

It roughly judges whether the given coordinates are within the mesh area.

Usage

```
eval_jp_boundary(longitude = NULL, latitude = NULL, ...)
```

Arguments

longitude	longitude that approximately to .120.0 to 154.0 (double)
latitude	latitude that approximately to 20.0 to 46.0 (double)
...	other parameters

Examples

```
eval_jp_boundary(139.71471056, 35.70128943)
```

export_mesh	<i>Export meshcode to geometry</i>
-------------	------------------------------------

Description

Convert and export meshcode area to `sfc_POLYGON` and `sf`.

Usage

```
export_mesh(meshcode)

export_meshes(meshcode, .keep_class = FALSE)
```

Arguments

meshcode	character. mesh code
.keep_class	Do you want to assign a class to the meshcode column in data.frame? If FALSE, it will be treated as a character type.

Value

`sfc` object
`sf` object

Examples

```
export_mesh("6441427712")
export_meshes("4128")
find_neighbor_mesh("37250395") |>
  export_meshes()
```

fine_separate	<i>Separate more fine mesh order</i>
---------------	--------------------------------------

Description

Return contains fine mesh codes

Usage

```
fine_separate(meshcode = NULL, .type = "standard", ...)
```

Arguments

meshcode	character. mesh code
.type	Specify the subdivision if you want to get a 100m mesh.
...	other parameters for paste

Value

meshcode

Examples

```
fine_separate("5235")
fine_separate("523504")
fine_separate("52350432")
fine_separate("523504321")
fine_separate("5235043211")
# to 100m mesh code
fine_separate("64414315", .type = "subdivision")
```

is_mesh	<i>Predict meshcode format and positions</i>
---------	--

Description

Predict meshcode format and positions for utility and certain.

Usage

```
is_meshcode(meshcode)

is_corner(meshcode)
```

Arguments

meshcode character. mesh code

jpnrect	<i>Simple displaed as rectangel for Japan (fortified)</i>
---------	---

Description

Rectangle Japanese prefectures positions.

Usage

```
jpnrect
```

Format

A data frame with 235 rows 11 variables:

- long
- lat
- order
- hole
- piece
- id
- group
- mesh_code
- latitude
- longitude
- abb_name

Examples

```
## Not run:  
plot(jpnrect["abb_name"])  
  
## End(Not run)
```

mesh_convert

Mesh unit converter

Description

Return different meshcode values included in the mesh.

Usage

```
mesh_convert(meshcode = NULL, to_mesh_size = NULL)
```

Arguments

meshcode character. mesh code
to_mesh_size target mesh size. That is, 1 for 1km, and 0.5 for 500m. From 80km to 0.100km.

Details

If NULL for to_mesh_size, the meshcode of one small scale will be returned. If it is the same as the original size, the meshcode of the input will be return.

Value

meshcode

Examples

```
mesh_convert(meshcode = "52350432", to_mesh_size = 80)
mesh_convert("52350432", 10)
# Scale down
mesh_convert("52350432", 0.500)
mesh_convert("52350432", 0.250)
mesh_convert(meshcode = "52350432", 0.125)
mesh_convert("523504323", 0.250)
mesh_convert("5235043213", 0.125)
mesh_convert(64414315, 0.1)
# Not changes
mesh_convert("52350432", 1)
mesh_convert("52350432131", 0.125)
```

mesh_size	<i>Identifier to mesh size</i>
-----------	--------------------------------

Description

Returns a unit object of mesh size for the given number.

Usage

```
mesh_size(meshcode, .type = "standard")
```

Arguments

- meshcode character. mesh code
- .type Specify the subdivision if you want to get a 100m mesh.

Examples

```
mesh_size("6740")
```

mesh_to_coords	<i>Get from mesh code to latitude and longitude</i>
----------------	---

Description

mesh centroid

Usage

```
mesh_to_coords(meshcode, ...)
```

Arguments

meshcode	character. mesh code
...	other parameters

References

Akio Takenaka: http://takenaka-akio.org/etc/j_map/index.html # nolint

See Also

[coords_to_mesh\(\)](#) for convert from coordinates to meshcode.

Examples

```
mesh_to_coords("64414277")
mesh_to_coords(c("64414277", "64414278"))
```

mesh_viewer	<i>interactive meshcode check</i>
-------------	-----------------------------------

Description

Shiny gadgets for jpmesh.

Usage

```
mesh_viewer(...)
```

Arguments

...	other parameters
-----	------------------

Examples

```
## Not run:
mesh_viewer()

## End(Not run)
```

meshcode_set	<i>Export meshcode vectors ranges 80km to 1km.</i>
--------------	--

Description

Unique 176 meshcodes. The output code may contain values not found in the actual mesh code.

Usage

```
meshcode_set(mesh_size = c(80, 10, 1), .raw = TRUE)
```

Arguments

mesh_size	Export mesh size from 80km to 1km.
.raw	return as character.

Value

character or [meshcode](#)

Examples

```
meshcode_set(mesh_size = 80)
meshcode_set(mesh_size = 80, .raw = FALSE)
```

meshcode_sf	<i>Conversion to sf objects containing meshcode</i>
-------------	---

Description

Convert and export meshcode area to sf.

Usage

```
meshcode_sf(data, mesh_var, .type, .keep_class = FALSE)
```

Arguments

<code>data</code>	<code>data.frame</code>
<code>mesh_var</code>	unquoted expressions for meshcode variable.
<code>.type</code>	Specify the subdivision if you want to get a 100m mesh.
<code>.keep_class</code>	Do you want to assign a class to the meshcode column in <code>data.frame</code> ? If <code>FALSE</code> , it will be treated as a character type.

Value

`sf` object

Examples

```
d <- data.frame(id = seq.int(4),
               meshcode = rmesh(4),
               stringsAsFactors = FALSE)
meshcode_sf(d, meshcode)
```

<code>meshcode_vector</code>	<i>Vector of meshcode</i>
------------------------------	---------------------------

Description

Vector of meshcode

Usage

```
meshcode_vector(x = character(), size = double(), .type = "standard")
```

```
meshcode(x, .type = "standard")
```

```
as_meshcode(x, ...)
```

```
## S3 method for class 'meshcode'
format(x, ...)
```

```
## S3 method for class 'subdiv_meshcode'
format(x, ...)
```

Arguments

<code>x</code>	input meshcode value
<code>size</code>	input meshcode size. Default set to <code>NULL</code> . The decision is automatically made based on the meshsize.
<code>.type</code>	Specify the subdivision if you want to get a 100m mesh.
<code>...</code>	path to another function

Value

meshcode

Examples

```
meshcode("6441")
meshcode(c("6441", "6442"))
meshcode(c("6441", "644143"))
meshcode("6441431552", .type = "subdivision")
```

neighbor_mesh	<i>Find out neighborhood meshes collection</i>
---------------	--

Description

input should use meshcode under the 1km mesh size.

Usage

```
neighbor_mesh(meshcode, contains = TRUE)

find_neighbor_mesh(meshcode = NULL, contains = TRUE)
```

Arguments

meshcode	character. mesh code
contains	logical. contains input meshcode (default TRUE)

Value

meshcode

Examples

```
neighbor_mesh(53394501)
neighbor_mesh(533945011)
neighbor_mesh(533945011, contains = FALSE)
```

rmesh	<i>Generate random sample meshcode</i>
-------	--

Description

Generate random sample meshcode

Usage

```
rmesh(n, mesh_size = 1)
```

Arguments

n	Number of samples
mesh_size	Export mesh size from 80km to 1km.

Value

meshcode

Examples

```
rmesh(3, mesh_size = 1)
```

sf_jpmesh	<i>1:200,000 Scale Maps Name with Meshcode of Japan.</i>
-----------	--

Description

Information for the 1:200,000 Scale Maps.

Usage

```
sf_jpmesh
```

Format

A data frame with 175 rows 9 variables:

- meshcode: 80km meshcode
- name: names for map
- name_roman: names for map (roman)
- lng_center: centroid coordinates of mesh
- lat_center: centroid coordinates of mesh
- lng_error: mesh area
- lat_error: mesh area
- type: evaluate value to mesh

Examples

```
## Not run:  
plot(sf_jpmesh["name_roman"])  
  
## End(Not run)
```

Index

- * **datasets**
 - jpnrect, [6](#)
 - sf_jpmesh, [13](#)
- administration_mesh, [2](#)
- as_meshcode (meshcode_vector), [11](#)
- coarse_gather, [3](#)
- coords_to_mesh, [3](#)
- coords_to_mesh(), [9](#)
- eval_jp_boundary, [4](#)
- export_mesh, [5](#)
- export_meshes (export_mesh), [5](#)
- find_neighbor_mesh (neighbor_mesh), [12](#)
- fine_separate, [5](#)
- format.meshcode (meshcode_vector), [11](#)
- format.subdiv_meshcode (meshcode_vector), [11](#)
- is_corner (is_mesh), [6](#)
- is_mesh, [6](#)
- is_meshcode (is_mesh), [6](#)
- jpnrect, [6](#)
- mesh_convert, [7](#)
- mesh_size, [8](#)
- mesh_to_coords, [9](#)
- mesh_to_coords(), [4](#)
- mesh_viewer, [9](#)
- meshcode, [3](#), [6](#), [8](#), [10](#), [12](#), [13](#)
- meshcode (meshcode_vector), [11](#)
- meshcode_set, [10](#)
- meshcode_sf, [10](#)
- meshcode_vector, [11](#)
- neighbor_mesh, [12](#)
- paste, [5](#)
- rmesh, [13](#)
- sf, [5](#), [11](#)
- sf_jpmesh, [13](#)
- sfc, [5](#)